

PROFESSIONAL SPECIFICATION | INDICATIVE TECHNICAL DATA

Black Angola Granite

Natural-stone reference selected by Marbre Import for architectural, interior and bespoke fabrication projects. Colour, veining and technical performance must be confirmed against the actual lot offered.



STONE FAMILY	Natural granite
ORIGIN / QUARRY AREA	Angola, Lubango region (formerly Sá da Bandeira)
APPEARANCE	Deep black, even texture, with black-to-brown reflections depending on the lot
PREDOMINANT COLOUR	Black
ALTERNATIVE TRADE NAMES	Angola Black Granite, Nero Angola, Black Angola, Angola Labrador and Granito Negro Angola
FORMATS AND FINISHES	Slabs, tiles, stair components, window sills and bespoke cut-to-size pieces. Available finishes include polished, honed, flamed, bush-hammered, brushed, leathered, sandblasted, split-face and natural, subject to project requirements.
RECOMMENDED APPLICATIONS	Worktops, floors, walls, staircases, memorials, fountains, pool copings, interior and exterior applications
EXTERIOR USE	Generally suitable, subject to the selected lot, finish, climate, installation method and application

Indicative technical properties

Bulk density	2 839 kg/m ³
Water absorption	0.02% by mass
Compressive strength	256-258 MPa
Flexural strength	25.2 MPa
Freeze-thaw / exterior use	Generally suitable, subject to finish, installation, climate and lot

SPECIFICATION NOTES

Approve the actual lot, finish, thickness, dimensions and vein layout before ordering. Performance ranges are indicative and may vary by quarry, batch and test method. Confirm suitability for exterior, wet-area, kitchen, façade or high-traffic use with the project team.

NON-CONTRACTUAL DOCUMENT - Natural variation is inherent to stone. Values, colour, movement and availability must be confirmed for the selected lot.